

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1. (Currently amended) A flow adjustment device for use with a blower comprising:

a base; ~~and~~

a plurality of blades coupled to said base;

wherein said flow adjustment device is one-touch attachable to said blower, and the blades are positioned in the form of a louver.

2. (Original) The flow adjustment device of Claim 1 wherein:

said blades are fixed; and

positioned radially around said base.

3. (Canceled)

4. (Currently amended) A flow adjustment device for use with a blower comprising:

a base; ~~and~~

a means for mounting said flow adjustment device to said blower;

a plurality of blades coupled to said base;

wherein said base is comprised of:

a plane surface; and

a turned-up wall surface.

5. (Canceled)

6. (Original) The flow adjustment device of Claim 4 further comprising:  
a protrusion centered on the plane surface of said base.

7. (Original) The flow adjustment device of Claim 4 further comprising:  
a cavity formed in the center of the plane surface of said base.

8. (Original) The flow adjustment device of Claim 4 further comprising:  
a plurality of pairs of projections extending from the planar surface of said base.

9. (Original) The flow adjustment device of Claim 8 wherein:  
said pairs of projections have hook-like latches.

10. (Original) The flow adjustment device of Claim 4 further comprising:  
a plurality of small holes in the planar surface of said base.

11. (Original) The flow adjustment device of Claim 4 further comprising:  
a plurality of notches in the turned up wall surface of said base.

12. (Original) The flow adjustment device of Claim 4 further comprising:  
a protrusion centered on the plane surface of said base;  
a plurality of pairs of projections extending from the plane surface of said  
base; and  
a plurality of notches in the turned up wall surface of said base.

13. (Currently amended) An axial flow blower comprising:

a blower casing;

a motor base having a plane surface;

a plurality of ribs for mounting said motor base to said blower casing;

a stator assembly affixed to said motor base;

a rotor assembly, including a plurality of fan blades rotatably mounted to said

motor base; and

a plurality of holes in said plane surface of said motor base adapted for one-touch attachment and detachment of a flow control device.

14. (Original) An axial flow blower comprising:

a blower casing;

a motor base having a plane surface;

a plurality of ribs for mounting said motor base to said blower casing;

a stator assembly affixed to said motor base;

a rotor assembly, including a plurality of fan blades, rotatably mounted to said

motor base; and

a plurality of protrusions extending from said plane surface of said motor base.

15. (Currently amended) A fan comprising:

~~a blower;~~

a flow adjustment device, having:

a base;

a means for mounting said flow adjustment device to said blower;

a plurality of blades coupled to said base,

wherein said base is comprised of

a plane surface; and

a turned-up wall surface; and

a blower having a means for one touch attaching said flow adjustment device to said blower.

16. (Currently amended) The fan of Claim 15 wherein:

said flow adjustment device can be ~~easily~~ detached from said blower.

17. (Currently amended) A fan comprising:

a blower;

a flow adjustment device;

a plurality of pairs of projections extending from said flow adjustment device; and

a ~~matching~~ plurality of openings matching each pair of projections in said blower.

18. (Currently amended) The fan of Claim 17 further comprising:

a means for centering said flow adjustment device with respect to said blower during the attachment of said flow adjustment device to said blower.[.]

19. (Original) A fan comprising:

- a blower;
- a flow adjustment device;
- a plurality of pairs of projections extending from said blower; and
- a matching plurality of openings in said flow adjustment device.

20. (Original) A fan comprising:

- a blower casing;
- a motor base having a motor base plane surface;
- a plurality of ribs for mounting said motor base to said blower casing;
- a stator assembly affixed to said motor base;
- a rotor assembly, including a plurality of fan blades, rotatably mounted to said motor base;
- a plurality of holes in said motor base plane surface;
- a blade base;
- a plurality of blades coupled to said blade base;
- wherein said blade base is comprised of:
  - a blade base plane surface;
  - a turned-up wall surface;
  - a protrusion centered on the blade base plane surface;
  - a plurality of pairs of projections extending from the blade base plane surface; and
  - a plurality of notches in the turned up wall surface.

21. (Currently amended) A method of adjusting a fan's airflow comprising the step of:

one-touch attaching an airflow adjustment device to a blower, where said airflow adjustment device comprises:

a base;

a means for mounting said flow adjustment device to said blower;

a plurality of blades coupled to said base,

wherein said base is comprised of

a plane surface; and

a turned-up wall surface.

22. (Currently amended) A method of attaching an airflow adjustment device to a blower comprising the steps of:

aligning the airflow adjustment device with the blower; and

pushing the airflow adjustment device into the blower, where said airflow

adjustment device comprises:

a base;

a means for mounting said flow adjustment device to said blower;

a plurality of blades coupled to said base,

wherein said base is comprised of

a plane surface; and

a turned-up wall surface.

23. (Currently amended) A method of manufacturing a fan comprising the steps of:

- obtaining a blower of a specific type;
- obtaining ~~a plurality of types of an~~ airflow adjustment ~~devices~~ device, wherein said airflow adjustment device comprises:
  - a base;
  - a means for mounting said flow adjustment device to said blower;
  - a plurality of blades coupled to said base,
  - wherein said base is comprised of
    - a plane surface; and
    - a turned-up wall surface;
- obtaining specific requirements for said fan; and
- ~~selecting an appropriate airflow adjustment device out of said plurality of types of~~  
~~airflow adjustment devices according to said specific requirements;~~
- attaching said appropriate airflow adjustment device to said blower.

24. (Original) A method of manufacturing a fan comprising the steps of:

- manufacturing a blower of a specific type;
- manufacturing a plurality of types of airflow adjustment devices;
- receiving an order for a fan where said order includes specific requirements for  
said fan;
- selecting an appropriate airflow adjustment device out of said plurality of types of  
airflow adjustment devices according to said specific requirements;
- shipping said appropriate airflow adjustment device and said blower.

25. (Original) The method of manufacturing according to Claim 24 wherein:  
said airflow adjustment device is attached to said blower prior to shipping.

26. (Currently amended) A method of adjusting a fan's airflow comprising the steps  
of:

removing a first airflow adjustment device; and

attaching a second airflow adjustment device, wherein at least one of said first and  
second airflow adjustment devices comprises:

a base;

a means for mounting said flow adjustment device to said blower;

a plurality of blades coupled to said base,

wherein said base is comprised of

a plane surface; and

a turned-up wall surface.